

# TECHNICAL DATASHEET

## Continuous mixing pump MIXPRO 30 plaster | ref.30848



Continuous mixing pump ideal for big construction sites.

Dry product separated from the mixing chamber and powder supply is made by wheel.

It is equipped with 4 steerable wheels for a better moving.

### APPLICATIONS

Floor screed, plaster, air insulation, fireproof products, light powders (polystyrene) ...

Products with instant kneading and no need for rest time.

Tank capacity	150 L
Electrical supply	230 V - 50 Hz
Thermal protection	yes
Geared-motor driving mixing arm	2,2 kW
Geared-motor powder wheel	0,5 kW
Compressor	yes
Compressor power	0,37 kW
Compressor air flow	12 m <sup>3</sup> /h
Variable speed	3 speeds
Water pump	yes
Flow-meter	plastic tube with float
Water safety switch	yes
Product pressure	0 to 25 bar
Product flow-rate	up to 26 L/min
Rotor/stator	T26 - 16 L/min
Spraying yield	28 bags of 33 kg/h
Spraying max. hose length	20 m
Loading height	91 cm
Dimensions (l x w x h)	111 x 67 x 155 cm
Weight	255 kg
Noise level	78 Lwa

### Delivered with

- a complete lance with aluminium pipe
- a Ø25 x 15 m product hose
- a Ø19 x 2 m pouring hose
- a Ø13 x 10 m air hose with GEKA
- a water hose Ø19 x 40 m with GEKA
- an electrical cable 20 m with plug
- a compressor
- an unplugging key
- a mixing tube cleaning part
- a mounting spray for rotor/stator
- two cleaning balls