

TECHNICAL DATASHEET

Exterior spraying machine COMPACT-PRO 45 E.W.I. version | ref.30559

Machine for spraying slurry, fibrous, decorative fillers, etc.

Compact-Pro 45 is a versatile sprayer.



APPLICATIONS

- glues and E.W.I. fillers
- thick plastic coatings
- light hydraulic fillers

Product pressure	0 to 40 bar
Product flow-rate	0 to 40 kg/min
Machine motor power	3 kW
Comp. absorbed air flow-rate	366 L/min
Compressor power	2,2 kW
Maximum air pressure	10 bar
Power supply	230 V - 20 A - 50 Hz
Tank capacity	100 L
Maximum grain size	3 mm
Pump	MAP 7
Integrated vibrator	yes
Dimensions (L x w x h)	130 x 70 x 75 cm
Weight	149 kg
Noise level	96 Lwa

Delivered with

- a Ø32 mm x 10 m air/product hose
- a pressure controller with adapter
- an E.W.I. carry case containing:
 - an E.W.I. aluminium spray lance
 - an air regulation kit
 - five spray nozzles (Ø6, 7, 8, 10 & 12 mm)
 - a grouting nozzle kit (Ø 10, 12 & 14 mm)
 - two cleaning balls
 - a cleaning brush
 - a 7 mm Allen key