

# TECHNICAL DATASHEET

## Continuous mixing pump MIXPRO 28 | ref.MI910000200B



Easy-to-use continuous mixing pump with a high yield.  
It can be disassembled in 4 parts, without tools, for a simplified transport.

### APPLICATIONS

Floor screed, plaster, air insulation, fireproof products, light powders (polystyrene) ...  
Products with instant kneading and no need for rest time.

Tank capacity	70 L
Electrical supply	230 V - 50 Hz
Thermal protection	yes
Geared-motor driving mixing arm	2,2 kW
Compressor	yes
Compressor power	1,1 kW
Compressor air flow	13 m <sup>3</sup> /h
Variable speed	no
Water pump	yes
Flow-meter	digital display
Water safety switch	yes
Product pressure	0 to 20 bar
Product flow-rate	up to 28 L/min
Rotor/stator	T26 - 16 L/min
Spraying yield	28 bags of 33 kg/h
Pouring yield	40 bags of 25 kg/h
Spraying max. hose length	20 m
Pouring max. hose length	100 m
Loading height	102 cm
Dimensions (L x w x h)	100 x 76 x 159 cm
Weight	120 kg

### Delivered with

- a complete spray lance with aluminium tube
- a Ø25 x 15 m product hose
- a Ø13 x 10 m air hose with GEKA
- a Ø19 x 40 m water hose with GEKA
- a 20 m electrical cable with plug
- a compressor on support plate