

# TECHNICAL DATASHEET

## Continuous mixing pump MIXPRO 50 | ref. MI903100930B



Continuous mixing pump ideal for big construction sites.

Dry product separated from the mixing chamber and powder supply is made by wheel.

It is equipped with 4 steerable wheels for a better moving.

### APPLICATIONS

Floor screed, plaster, air insulation, fireproof products, light powders (polystyrene) ...

Products with instant kneading and no need for rest time.

Tank capacity	150 L
Electrical supply	400 V - 50 Hz
Thermal protection	yes
Electrical box	IP 67
Geared-motor driving mixing arm	5,5 kW
Geared-motor powder wheel	0,5 kW
Compressor	yes
Compressor power	0,9 kW
Compressor air flow	15 m <sup>3</sup> /h
Variable speed	no
Water pump	yes
Flow-meter	plastic tube with a float
Water safety switch	yes
Product pressure	0 to 25 bar
Product flow-rate	up to 50 L/min
Rotor/stator	T2 - 27 L/min
Spraying yield	34 bags of 33 kg/h
Pouring yield	60 bags of 25 kg/h
Spraying max. hose length	35 m
Pouring max. hose length	150 m
Loading height	91 cm
Dimensions (L x w x h)	111 x 67 x 155 cm
Weight	260 kg

### Delivered with

- a complete spray lance with aluminium tube
- a Ø25 x 15 m product hose
- a Ø13 x 10 m air hose with GEKA
- a Ø19 x 40 m water hose with GEKA
- a 50 m electrical cable with plug
- a compressor