

DYNAMIC MIXER WITH DISPOSABLE MIXING CHAMBER AND TWO COMPONENT SWIVEL JOINT FOR INTEGRATION INTO MANUAL SEALING PLANTS



ECONOMIC BENEFITS

SAVINGS OF OPERATING EXPENSES UP TO € 15.000,- PER YEAR THROUGH:

Dimensions	Length	Width	Height
	700 mm	80 mm	100 mm
Admissible operating pressure	200 bar		
Output	450 - 1000 ccm/min		
Air pressure	6 bar		
Weight approx.	4150 g		

Optionally available as integrated in Ecostar evo series or as
retro-fit kit for existing installations.

- **Freezer or solvent flushing pump no longer required**
- **No more loss of material through purging processes**
- **Saving of costs for disposal of waste material**
- **No more necessity for cleaning of Z-swivel joint**
- **No complementary purchase of trumpet mixer required**
- **Less wear of the plant by lowering the pressure level to approximately 120 bar**

YOUR GLOBAL PARTNER FOR METERING AND MIXING TECHNOLOGY

- Processing and application of single and multi component adhesive and sealants as well as casting/encapsulation liquids.
- Ambient and temperature conditioned equipment
- Complete systems for manual or fully automatic processes
- Innovative process control and verification



We look forward to discuss further details with you.

Reinhardt-Technik GmbH

Waldheimstraße 3 T +49 (0) 23 59 - 6 66.0 info@reinhardt-technik.de
58566 Kierspe/Germany F +49 (0) 23 59 - 6 66.1 29 www.reinhardt-technik.de

 **WAGNER** GROUP