

TECHNICAL DATASHEET

Exterior spraying machine COMPACT-PRO 15 | ref.30870

Machine for spraying slurry, fibrous, decorative fillers, etc.
Compact-Pro 15 is a small versatile sprayer.



APPLICATIONS

Exterior:

- glues and E.W.I. fillers
- thick plastic coatings
- light hydraulic fillers (occasional)

Interior:

- levelling fillers
- droplet plasters

Product pressure	0 to 20 bar
Product flow-rate	0 to 15 kg/min
Machine motor power	1,5 kW
Comp. absorbed air flow-rate	366 L/min
Compressor power	2,2 kW
Maximum air pressure	10 bar
Power supply	230 V - 16 A - 50 Hz
Tank capacity	59 L
Maximum grain size	2 mm
Pump	MAP 3
Integrated vibrator	no
Dimensions (L x w x h)	108 x 64 x 73 cm
Weight	98 kg
Noise level	96 Lwa

Delivered with

- a Ø25 mm x 10 m air/product hose
- an E.W.I. carry case containing:
 - an ABS E.W.I. spray lance
 - air pressure adjustment
 - a threaded ring for grouting nozzles
 - five spray nozzles (Ø6, 7, 8, 10 & 12 mm)
 - a grouting nozzle kit (Ø 10, 12 & 14 mm)
 - two cleaning balls and a tube brush
 - a 7 mm Allen key