

# TECHNICAL DATASHEET

## Exterior spraying machine COMPACT-PRO 40 mortar version | ref.30790

Spraying machine for mortars and exterior coatings. Equipped with a stainless steel tank, a vibrator, a digital control panel and a mono-cylinder compressor.

### APPLICATIONS

Traditional mortars with admixtures, hydraulic coatings, monolayers, lime-based coatings, high-load technical and special coatings, repointing coatings...



Product pressure	0 to 20 bar
Product flow-rate	0 to 40 kg/min
Machine motor power	3 kW
Comp. absorbed air flow-rate	284 L/min
Compressor power	2,2 kW
Maximum air pressure	10 bar
Power supply	230 V - 16 A - 50 Hz
Tank capacity	100 L
Maximum grain size	3 mm
Pump	MAP 6
Integrated vibrator	yes
Dimensions (L x w x h)	130 x 70 x 75 cm
Weight	141 kg
Noise level	94 Lwa

### Delivered with

- a Ø32 mm x 20 m air/product hose
- a pressure controller with adapter
- a carry-case containing:
  - an ABS mortar spray lance
  - eight spray nozzles (Ø8, 10, 12, 14, 16, 18, 20 & 22 mm)
  - three grouting nozzles (Ø10, 12 and 14 mm)
  - two cleaning balls and a tube brush
  - a cleaning brush
  - an unplugging brush
  - a 7 mm Allen key