

TECHNICAL DATASHEET

Exterior spraying set

PROJECT CP 35 E.W.I. version + PREMIUM mixer | ref.EC3033



Special E.W.I. set, composed with a spraying machine and a sequential mixer.

A vibrator is attached to the tank of the machine for a better descent of the product towards the bottom.

The mixer is equipped with a double helical paddle on a horizontal arm which ensures a rapid and homogeneous mixing, a water doser, a speed control and a rotation direction reversing function.

APPLICATIONS

Wide variety of applicable products including powder and ready-to-use.

Exterior:

- glues and E.W.I. fillers
- thick plastic coatings
- light hydraulic fillers
- fireproofing mortars
- repair mortars
- insulation plasters

Product pressure	0 to 50 bar
Product flow-rate	0 to 30 kg/min
Machine motor power	2,2 kW
Comp. absorbed air flow-rate	366 L/min
Compressor power	2,2 kW
Power supply	230 V - 16 A - 50 Hz
Machine tank capacity	100 L
Maximum grain size	3 mm
Integrated vibrator	yes
Pump	MAP 7
Mixer motor	1,1 kW
Mixer tank capacity	70 L
Machine dim. (L x w x h)	130 x 70 x 75 cm
Mixer dim. (L x w x h)	88 x 52 x 57 cm
Machine weight	143 kg
Mixer weight	75 kg
Noise level	96 Lwa

Delivered with

- a Ø32 mm x 20 m air/product hose
- an air/product easy handling extension hose Ø25 x 5 m
- a cleaning slide
- a suspension strap
- a pressure controller with adapter
- a carry-case containing:
 - an aluminium-E.W.I. spraying lance
 - an air adjustment kit
 - a threaded ring for grouting nozzles
 - three grouting nozzles Ø 10, 12 & 14 mm
 - five spraying nozzles n°6, 7, 8, 10 & 12
 - two cleaning balls
 - a 7 mm Allen key
 - a tube brush